

TAURUSTM

MULTI

HCL-5000D

DIGITAL HV-CURRENT CLAMP TESTER

ϕ 35 AC 600A DATA HOLD AUTO POWER OFF



FEATURES

- Wide Range Measurement of 0.1A~600A.
- Easy Operation - Push & Pull Auto Opening/ closing CT
- Safety Design & Function
- Auto Power off Function & Watertight Proof Structure.

SPECIFICATIONS

Measuring Function	: AC line current
Measuring Method	: Dual integration mode
Display	: 3.5 digit LCD max. reading of 1999 with annunciators
Measuring Range	: 0~20A/600A manual (50Hz or 60Hz)
Jaw opening Capability	: ϕ 35mm
Data hold Function	: "DH" mark on LCD
Auto Power off	: Automatically power off mode, approx. 5minutes after the power switch on.
Sampling time	: 2 times/sec
Low Battery Indication	: [B] mark on LCD.
Operating Temperature	: 0~40°C, less than 80%RH without condensing
Power supply	: Battery UM-4×2
Size & Weight	: 70(W)×356(H)×68(D)mm, approx.400gs.
Accessories	: Carrying Case.....1pce. Instruction manual.....1pce.

Accuracy

Range	Resolution	Accuracy
20A	0.01A	$\pm 2\% \text{rdg} \pm 8 \text{dgt}$
600A	1A	$0 \sim 400A \sim \pm 2\% \text{rdg} \pm 9 \text{dgt}$ $400A \sim 600A \sim \pm 3\% \text{rdg} \pm 10 \text{dgt}$



An ISO 9001 : 2015 Company

TAURUS POWERTRONICS PVT LIMITED

Corporate Off.: No. 26, "Mahadimane", 12th Main, 1st Block, Rajajinagar, Bengaluru - 560 010. INDIA. Tel : + 91 80 23012301

Email : info@tauruspowertronics.com, care@tauruspowertronics.com, Tollfree : 1800 425 2112, WhatsApp : +91 73496 44344

Sales & Service Off.: No. 648/54, KLE College 2nd Block, Rajajinagar, Bengaluru - 560 010. INDIA , Tel : + 91 80 2352 2136/74

BENGALURU

DELHI

KOLKATA

MUMBAI

www.tauruspowertronics.com