



Model M-220

φ 33
AC 200A
DATA HOLD



FEATURES

- 33mmØ CT window, and ultra compact size
- Data-hold function. Especially useful when working in dark or hard to get areas.
- Conform to IEC safety requirements.

SPECIFICATIONS

Safety standard	: IEC 61010-1 , IEC 61010-2-032 CAT II 600V , CAT III 300V
E.M.C. standard	: EN 61326
Measuring method	: Dual integration mode
Display	: 3.5 digit LCD max. reading of 1999
Jaw opening capability	: 33 mmφ
Over range indication	: Blanking of all digits except MSD1
Maximum indication	: 1999
Low battery indication	: "B" mark on LCD
Data hold indication	: "DH" mark on LCD
Sampling time	: 2 times/sec
Withstanding voltage	: AC 3700V 1 minute max. (Between the core of CT and outer case)
Operating temperature	: 0°C to +40°C<80%RH
Storage temperature	: -10°C to +60°C<70%RH
Power supply	: SR-44 (1.55V) ×2 or LR-44 ×2
Power consumption	: 3mW
Battery life	: SR-44 (200 hours), LR-44 (100 hours)
Size	: 54(W)×167(H)×23(D)mm
Weight	: Approx. 100g
Accessories	: Soft case 1 : Instruction manual 1 : Batteries, LR-44(1.55V) .. 2

Accuracy

Range	Resolution	Accuracy
20A	10mA	±1.2% rdg ±5dgt (50/60Hz)
200A	100mA	



An ISO 9001 : 2015 Company

TAURUS POWERTRONICS PVT LIMITED

Corporate Off.: No. 26, "Mahadimane", 12th Main, 1st Block, Rajajinagar, Bengaluru - 560 010. INDIA. Tel : + 91 80 23012301

Email : info@tauruspowertronics.com, care@tauruspowertronics.com, Tollfree : 1800 425 2112, WhatsApp : +91 73496 44344

Sales & Service Off.: No. 648/54, KLE College 2nd Block, Rajajinagar, Bengaluru - 560 010. INDIA , Tel : + 91 80 2352 2136/74

BENGALURU

DELHI

KOLKATA

MUMBAI