TAURUS

MULTI

HCL-3000D

DIGITAL HV-CURRENT CLAMP TESTER

ϕ 35 | AC 20A | DATA HOLD | AUTO POWER OFF

FEATURES

- Low Range Measurement of 1mA~20A in Hi-Voltage Circuit upto 7KV
- Easy Operation - Push & Pull Auto Opening/ closing CT
- Safety Design & Function
- Auto Power off Function & Waterdrop Proof Structure

SPECIFICATIONS

Measuring Function	:	AC leakage/line current
Measuring Method	:	Dual integration mode
Display	:	3.5 digit LCD max. reading of 1999 with annunciators
Measuring Range	:	0~2000mA/20A manual (50Hz or 60Hz)
Jaw opening Capability	:	φ35mm
Data hold Function	:	"DH" mark on LCD
Auto Power off	:	Automatically power off mode, approx.5minutes after the power switch on.
Sampling time	:	2 times/sec
Low Battery Indication	:	[B]mark on LCD.
Operating Temperature	:	0~40°C, less than 80%RH without condensing
Power supply	:	Battery UM-4×2
Size & Weight	:	70(W)×356(H)×68(D)mm,approx. 370gs.
Accessories	:	Carrying Case.....1pce. Instruction manual.....1pce.

Accuracy

Range	Resolution	Accuracy
2000mA	1mA	±2%rdg±8dgt
20A	0.01A	±2%rdg±8dgt

TAURUS
Innovative Technologies
An ISO 9001 : 2015 Company

TAURUS POWERTRONICS PVT LIMITED

Corporate Off.: No. 26, "Mahadimane", 12th Main, 1st Block, Rajajinagar, Bengaluru - 560 010. **INDIA., Tel :** + 91 80 23012301
Email : info@tauruspowertronics.com, care@tauruspowertronics.com, **Tollfree :** 1800 425 2112, **WhatsApp :** +91 73496 44344
Sales & Service Off.: No. 648/54, KLE College 2nd Block, Rajajinagar, Bengaluru - 560 010. INDIA , **Tel :** + 91 80 2352 2136/74

BENGALURU
DELHI
KOLKATA
MUMBAI