

FIELD MEASURING INSTRUMENTS FOR PV SYSTEM

MULTI CIRCUIT DC CURRENT MONITOR (16 CHANNELS)

Model MCM-1600PV



Measuring + display of DC current values generated by PV systems and DC load current of related apparatus in multi circuit successively for a long term as well as memorizing the average current values between the intervals, of which data can be transmitted to PC in Excel File.

The circuits to be measured are max. 16 lines and in PV systems, can measure DC current per each string unit at the same time.

Using clamp type current sensors which enable safe and easy operation.

Measure • Memorize • Display The DC Current of Max. 16 Circuits at the same time.

Easy for Data Management (storage by csv formula).

GENERAL

1. MEASURING FUNCTION

By Connecting Optional CT Sensors, the instrument can Measure and memorize DC current of 16 circuit at the Same time and the memorized data can be seen even During measurement.

2. LOGGING MEASURING FUNCTION

This instrument displays and memorizes the average current between the selected intervals.

Interval : 1 / 5 / 10 / 15 / 30 / 60 minutes

Contents of Memory : Measuring Time / Measuring Circuit / The average current value

Capacity of Memory : Approx. 20,000 data (72 days with 5 minutes interval)

3. OTHER FUNCTION

Over Range Indication : "OL" mark on LCD, Low Battery Indication : "B" mark on LCD,

Logging Mode Indication : "R" mark on LCD

Auto Power Off : Approx. 10 minutes after last key operation. (this function will not be active in case of using AC adopter, timer set on and logging mode)

SPECIFICATIONS

Number of Measuring Circuit	: 16 Circuits (channels)
Detection Method	: Clamp-on CT Method
Measuring Range	: DC0~99.9A
Minimum Resolution	: 0.1A
Measuring Accuracy	: $\pm 3\%rdg \pm 5dgt$
Sampling	: Approx. 20mS
Measuring Temperature	: 0~50°C, less than 80%RH w/o condensing
Storage Temperature	: -10~60°C, less than 80%RH w/o condensing
Measuring Circuit Voltage	: less than DC600V (insulated conductor)
Insulation Resistance	: more than 100MΩ by DC500V insulation tester (between input terminal and housing case) more than 50MΩ by DC500V insulation tester (between power supply source and housing case)
Withstanding Voltage	: AC2200V (50 / 60Hz) one minute between power supply source and housing case
Power Supply	: AC100V~240V with adapter Internal Ni-hydrate Battery
Battery Life	: Approx. 4 days at continuous use by full charge
Dimensions & Weight	: 236(W)×170(H)×56(D)mm, approx. 840gs
Standard Accessories	: Carrying Case, AC Adapter, USB Cable, Instruction Manual
Optional Accessories	: CT-30PV Clamp CT with i.d. 30mm & 2.8m cable, CT Carrying Case (for max. 8 Cts)



Innovative Technologies

An ISO 9001 : 2015 Company

TAURUS POWERTRONICS PVT LIMITED

Corporate Off.: No. 26, "Mahadimane", 12th Main, 1st Block, Rajajinagar, Bengaluru - 560 010. INDIA. Tel : + 91 80 23012301

Email : info@tauruspowertronics.com, care@tauruspowertronics.com, Tollfree : 1800 425 2112, WhatsApp : +91 73496 44344

Sales & Service Off.: No. 648/54, KLE College 2nd Block, Rajajinagar, Bengaluru - 560 010. INDIA, Tel : + 91 80 2352 2136/74

BENGALURU

DELHI

KOLKATA

MUMBAI