

MULTI

DIGITAL INSULATION RESISTANCE TESTER

For 3 Range Insulation Measurements

Model MIS-4D

125V/20M Ω , 250V/50M Ω , 1000V/2000M Ω



FEATURES

- The big digital and bargraph LCD display with back light enabled easy observation. Especially useful when working in dark place.
- Hand free and continuous measurements with custom made switch.
- Safe design with built in automatic discharging function for any capacitors present in the circuit.
- The voltage in the circuit or capacitor can be checked by warning lamp for safe insulation measurements.
- Data hold and auto power off function.
- Compact, light weight and heavy duty rugged case.

SPECIFICATIONS

Function	: Insulation resistance, AC voltage
Display	: 3½ digit LCD with bargraph display, max. reading of 3200 count & annunciators
Response time	: Less than 5 sec. (Auto ranging)
Data hold indication	: "DH" mark on LCD readout
Infinity indication	: "OL(∞)" mark on LCD readout (Over 3200 count)
Safety standard	: IEC 61010-1, CAT II, 600V
E.M.C. standard	: EN 61326
Constructional standard	: IEC 61557-2
Insulation resistance	: DC 1000V-50M or more
Withstanding voltage	: AC 3700V, 1 minute (Between input terminal and outer case)
Overload protection	: 120% of the highest nominal output voltage (10sec.)
Low battery indication	: "B" mark on LCD readout
Temperature characteristics (0~40°C)	: $\pm 5\%$ rdg of specified accuracy
Operating temperature	: 0°C to 40°C, 80% RH max. (Non-condensing)
Storage temperature	: -10°C to 60°C, 80% RH max. (Non-condensing)
Power supply	: 1.5V("AA" size, LR6) \times 6
Size	: 170 (W) \times 105(D) \times 54(H)mm
Weight	: Approx. 365g (Excluding batteries)
Accessories	: Line Test Lead.....1, Earth Test Lead.....1, Batteries.....6, Test Lead Case.....1, Belt.....1, Instruction Manual ...1
Optional accessory	: Remote switch test lead

Measuring Ranges and Technical Data - Insulation Resistance Measurement

Model	MIS-4D
Rated voltage & effective measuring range	125V-20MΩ 250V-50MΩ 1000V-2000MΩ
Minimum measurable resistance at rated voltage	0.125MΩ 0.25MΩ 1MΩ
Rated current	1mA+20%-0%
Maximum no-load voltage	Rated Voltage+30%-0%
Short circuit current	<2mA

Accuracy

Rated Voltage	DC 125V	DC 125V	DC 250V	DC 500V
	0~20MΩ~0L(∞)	0~50MΩ~0L(∞)	0~100MΩ~0L(∞)	0~2000MΩ~0L(∞)
First effective range	0.02MΩ~10MΩ <±5%rdg	0.05MΩ~20MΩ <±5%rdg	0.1MΩ~50MΩ <±5%rdg	2MΩ~1000MΩ ±5%rdg
Second effective range	0.01MΩ~0.02MΩ 10MΩ~100MΩ <±10%rdg	0.02MΩ~0.05MΩ 20MΩ~100MΩ <±10%rdg	0.05MΩ~0.1MΩ 50MΩ~100MΩ <±10%rdg	1MΩ~2MΩ 1000MΩ~2000MΩ <±10%rdg
Other range	100MΩ~0L(∞) Not specified			2000MΩ~0L(∞) Not specified

AC Voltage Measurement (50/60Hz)

Range	Accuracy	Input impedance	Maximum input voltage
AC 600V	±2.5% of full scale	Approx.2.0MΩ	AC 600V rms



TAURUS POWERTRONICS PVT LIMITED BENGALURU

Corporate Off.: No. 26, "Mahadimane", 12th Main, 1st Block, Rajajinagar, Bengaluru - 560 010. INDIA., Tel : + 91 80 23012301

Email : info@tauruspowertronics.com, enquiry@tauruspowertronics.com, WhatsApp : +91 73496 44344

Sales & Service Off.: No. 648/54, KLE College 2nd Block, Rajajinagar, Bengaluru - 560 010. INDIA , Tel : + 91 80 2352 2136/74

DELHI
KOLKATA
MUMBAI